

Printing date 31.10.2018 Version number 303 Revision: 31.10.2018

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier 600002

· Trade name: Drilling and Cutting Oil Spray E-COLL

· Article number: 4317784464895

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Application of the substance / the mixture Lubricant
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

E/D/E - Einkaufsbuero Deutscher Eisenhaendler GmbH EDE Platz 1 D-42389 Wuppertal Germany

Tel. +49 202 6096-0 e-mail: sdb@ede.de

- · Further information obtainable from: Product safety department
- · 1.4 Emergency telephone number: Giftinformationszentrum Mainz Tel.: +49 (6131) 19240

### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

- · 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



· Signal word Danger



Printing date 31.10.2018 Version number 303 Revision: 31.10.2018

Trade name: Drilling and Cutting Oil Spray E-COLL

(Contd. of page 1)

#### · Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

#### · Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

#### · 2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· vPvB: Not applicable.

#### **SECTION 3: Composition/information on ingredients**

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

<ul> <li>Dangerous components:</li> </ul>			
CAS: 115-10-6	dimethyl ether	♦ Flam. Gas 1, H220; Press. Gas C, H280	25-50%
EINECS: 204-065-8			
Index number: 603-019-00-8			
Reg.nr.: 01-2119472128-37-xxxx			

· Additional information: For the wording of the listed hazard phrases refer to section 16.

### **SECTION 4: First aid measures**

#### · 4.1 Description of first aid measures

- · After inhalation: Supply fresh air.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)



Printing date 31.10.2018 Version number 303 Revision: 31.10.2018

Trade name: Drilling and Cutting Oil Spray E-COLL

(Contd. of page 2)

• 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

#### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: Do not inhale explosion gases or combustion gases.
- · Additional information Cool endangered receptacles with water spray.

#### **SECTION 6: Accidental release measures**

6.1 Personal precautions, protective equipment and emergency procedures
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation

#### · 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.

- · 6.3 Methods and material for containment and cleaning up: Ensure adequate ventilation.
- · 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### **SECTION 7: Handling and storage**

- · 7.1 Precautions for safe handling Use only in well ventilated areas.
- · Information about fire and explosion protection:



Keep ignition sources away - Do not smoke.

Do not spray onto a naked flame or any incandescent material.



Printing date 31.10.2018 Version number 303 Revision: 31.10.2018

Trade name: Drilling and Cutting Oil Spray E-COLL

(Contd. of page 3)

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Store away from oxidising agents.
- · Further information about storage conditions:

Keep container tightly sealed.

Protect from heat and direct sunlight.

· 7.3 Specific end use(s) No further relevant information available.

#### **SECTION 8: Exposure controls/personal protection**

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

CAS: 115-10-6 dimethyl ether

IOELV Long-term value: 1920 mg/m³, 1000 ppm

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures: Wash hands before breaks and at the end of work.
- · Respiratory protection: Not necessary if room is well-ventilated.
- · Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Recommendation: protective gloves

### Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm



Printing date 31.10.2018 Version number 303 Revision: 31.10.2018

Trade name: Drilling and Cutting Oil Spray E-COLL

(Contd. of page 4)

#### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

### **SECTION 9: Physical and chemical properties**

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Aerosol
Colour: Light yellow
Odour: Characteristic
Odour threshold: Not determined.

· **pH-value:** Not determined.

· Change in condition

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: Not applicable, as aerosol.

· Flash point: Not applicable, as aerosol.

· Flammability (solid, gas): Not applicable.

· Ignition temperature: 235 °C

· **Decomposition temperature:** Not determined.

· Auto-ignition temperature: Product is not selfigniting.

• Explosive properties: Product is not explosive. However, formation of explosive air/

vapour mixtures are possible.

· Explosion limits:

Lower: 3.0 Vol %
Upper: 18.6 Vol %
• Oxidising properties Not determined.

· Vapour pressure at 20 °C: 5200 hPa

(Contd. on page 6)



Printing date 31.10.2018 Version number 303 Revision: 31.10.2018

Trade name: Drilling and Cutting Oil Spray E-COLL

(Contd. of page 5)

· Density at 20 °C: 0.78 g/cm<sup>3</sup>

· Relative density Not determined.

Vapour densityEvaporation rateNot determined.Not applicable.

· Solubility in / Miscibility with

water: Not miscible or difficult to mix.

· Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

**Dynamic:** Not determined. **Kinematic:** Not determined.

 Organic solvents:
 50.0 %

 VOC (EC) %
 390,0 g/l

• 9.2 Other information No further relevant information available.

### **SECTION 10: Stability and reactivity**

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:
   No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

#### **SECTION 11: Toxicological information**

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

CAS: 115-10-6 dimethyl ether

Inhalative LC50/4h 308 ppm (rat)

(Contd. on page 7)



Printing date 31.10.2018 Version number 303 Revision: 31.10.2018

Trade name: Drilling and Cutting Oil Spray E-COLL

(Contd. of page 6)

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

#### **SECTION 12: Ecological information**

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Harmful to aquatic organisms

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.



Printing date 31.10.2018 Version number 303 Revision: 31.10.2018

Trade name: Drilling and Cutting Oil Spray E-COLL

(Contd. of page 7)

- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

#### **SECTION 13: Disposal considerations**

#### · 13.1 Waste treatment methods:

Containers can be recycled if completely empty; if not, dispose product/containers as dangerous waste. Observe local regulations.

#### · Recommendation

Completely emptied packagings can be given for recycling. (In accordance with local authority regulations, take to chemical/physical treatment plant.)

· European waste catalogue			
16 05 04*	gases in pressure containers (including halons) containing hazardous substances		
15 01 10*	packaging containing residues of or contaminated by hazardous substances		

### **SECTION 14: Transport information**

· 14.1 UN-Number

· ADR, IMDG, IATA UN1950

· 14.2 UN proper shipping name

· ADR UN1950 AEROSOLS

· IMDG AEROSOLS

· IATA AEROSOLS, flammable

- · 14.3 Transport hazard class(es)
- · ADR



· Class 2 5F Gases.

· Label 2.1

· IMDG, IATA



· Class· Label2.12.1

· 14.4 Packing group

· IMDG, IATA Void

(Contd. on page 9)



Printing date 31.10.2018 Version number 303 Revision: 31.10.2018

Trade name: Drilling and Cutting Oil Spray E-COLL

(Contd. of page 8)

· 14.5 Environmental hazards:

· Marine pollutant: No

• 14.6 Special precautions for user Warning: Gases.

· Danger code (Kemler):

• EMS Number: F-D,S-U

· 14.7 Transport in bulk according to Annex II of

Marpol and the IBC Code Not applicable.

· Transport/Additional information:

· ADR

Limited quantities (LQ)Excepted quantities (EQ)Code: E0

Not permitted as Excepted Quantity

Transport categoryTunnel restriction code

· IMDG

Limited quantities (LQ)Excepted quantities (EQ)Code: E0

Not permitted as Excepted Quantity

• UN "Model Regulation": UN1950, AEROSOLS, 2.1

#### **SECTION 15: Regulatory information**

- · Directive 2012/18/EU
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

### · Relevant phrases

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

· Department issuing SDS: Product safety department

· Contact: sdb@ede.de



Printing date 31.10.2018 Version number 303 Revision: 31.10.2018

Trade name: Drilling and Cutting Oil Spray E-COLL

(Contd. of page 9)

#### · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the

International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Gas 1: Flammable gases – Category 1 Aerosol 1: Aerosols – Category 1

Press. Gas C: Gases under pressure - Compressed gas

· \* Data compared to the previous version altered.

FU -